

FMP-900-N or P  
 Double Rack Gas Baking Oven  
 FMP Equipment Corp.  
 Greensboro, NC 27415  
 336-621-2882

**Key**

- 1 - Hood Exhaust 8.00 Diameter
- 2 - 3 Ph. Electric Service

240/480 Volt\*

10/5 Amp\*

\*240V **OR** 480V to be specified upon order entry

60 Hz.

- 3 - 1 Ph. Electric Service

120 Volt, 60 Hz

20 Amp dedicated circuit

Oven Control: 3 Amp (Clean Power)

Ventilator connect point: 10 Amp, 1/3 HP

- 4 - Water Service 1/4" NPT

Cold Water @ 45 PSI min. @ 4.5 GPM flow rate

- 5 - Choose lower left or rear corner drain.

Route to air gap drain

- 6 - Powered Hood Exhaust W / Downdraft Preventive Cap  
 750 CFM Reqd. (.5" w.c. static pressure drop through hood)

Customer to supply duct and ventilator fan per local code. Consult local authorities to determine whether TYPE I (meats) or TYPE II (no grease) duct and ventilator fan will be required. Products of combustion and chamber vents are factory ducted to this integral hood. Airflow proving switch is factory installed.

- 7 - 1/2" NPT Gas Service

180,000 BTU/Hr

- 8 - Weight Approximately 1700 Lbs.

NOTE: Purchaser is responsible for all installation costs and for providing:  
 Labor to unload oven upon arrival.  
 Installation Mechanics.

All local service connections including:  
 electricity, vents, water & drain per local code.

**A FACTORY TECHNICIAN OR FACTORY AUTHORIZED INSTALLATION TECHNICIAN MUST SUPERVISE AND / OR APPROVE ANY INSTALLATION!**

**CAUTION:**

- Use **ONLY** on specially constructed noncombustible floors. See Installation Instructions
- Exhaust Duct Installation **MUST** be in accordance with NFPA 96 and/or Local Codes.

